



Art. No.: 31298
Ambus EasySwitch Class CC
holder for cylindrical fuses Class CC
1-pole
with luminous indication

Product Group : 17
Subgroup : 07

Standards :
UL 512
CSA C22.2 No. 39

Approvals :
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: AES CC
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, www.ul.com
CSA File Number: 110285, Class Number: 6225-01, <http://directories.csa-international.org>

Electrical Data :
30 A, 600 V (60 Hz)
rated insulation voltage : 800 V
for fuse links Class CC to UL 248-4

luminous indication
range of operating voltage: 110 - 600 V AC / DC

Mechanical Data :
Width x Height x Depth (mm): 18 x 81 x 58
Weight (kg/100): 6,7

Mechanical Data :

Fastening method:
clip-on mounting

Connections :

box terminal :
1,5 - 25 mm² / AWG 16 - AWG 4
flexible cables, directly or with wire-end ferrule
Md 2,0 - 2,5 Nm / 18 - 22 lb.in.
(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

Versions :

version without luminous indication : part no. 31295

Pack Size : 12

Catalog 2006 :

Page: 6/8

Accessories to Article 31298 :



31939 label for AES
100x 10 pcs.